



Instructions for “bottom-up” roller blind installation.

- 1) Install brackets with clutch bracket on left.
- 2) Install stoppers at point about 10-15cm up from the bottom of the window.
- 3) Use these when the blind is in the “down” position.
- 4) Select the height for the blind in the “up” position and install stoppers. Extra stoppers are available if you want more than one “up” position.
- 5) Put approximately 10 turns in an anticlockwise direction with the clutch on the left and fabric at the back (as it will be when it is being used).
- 6) Hold the clutch and put it into the left hand bracket. The pin end just pushes in.
- 7) Test tension and add more or less as needed.



Stopper.



Blind in up position



Install clutch
See stopper in down position

www.petermeyerblind.com.au



Instructions for “bottom-up” roller blind installation.

- 1) Install brackets with clutch bracket on left.
- 2) Install stoppers at point about 10-15cm up from the bottom of the window.
- 3) Use these when the blind is in the “down” position.
- 4) Select the height for the blind in the “up” position and install stoppers. Extra stoppers are available if you want more than one “up” position.
- 5) Put approximately 10 turns in an anticlockwise direction with the clutch on the left and fabric at the back (as it will be when it is being used).
- 6) Hold the clutch and put it into the left hand bracket. The pin end just pushes in.
- 7) Test tension and add more or less as needed.



Stopper.



Blind in up position



Install clutch
See stopper in down position

www.petermeyerblind.com.au